
Solidly Engineered Hardwood Flooring





Owens' **state-of-the-art facilities** are located in northern Wisconsin, in the heart of some of the best hardwood forests in North America. There, Owens combines high quality Baltic birch plywood with a solid hardwood wear layer to create a truly remarkable engineered flooring product. Owens coined the term Plankfloor to describe it. Plankfloor has **revolutionized** the way hardwood flooring is specified, installed, and finished.

The slogan "Solidly Engineered" is often used to describe Plankfloor.

Unlike thin laminates, the sawn, (not peeled) 3/16" (4.5mm) wear layer can be sanded and refinished just like solid product.

As a result, the life expectancy, and installed appearance, is indistinguishable from traditional 3/4" flooring.

Plankfloor is incredibly versatile and will provide a **variety of designer looks**. It is offered in widths as narrow as 2 1/4" and as wide as 8". Lengths are random, 1' to 8' or custom 2' to 10'. It can be installed on any level of the home, even **directly over concrete**.

Owens' Prefinished version of this brilliant line, is coated with extremely durable **Aluminum Oxide UV finish**. This specially formulated coating boasts a 35 year residential, wear through, warranty.



9-ply Baltic Birch



TABLE OF CONTENTS



Genuine Living Collection



TrueCharacter Collection



Plankfloor Collection 16


Species & Grades 34

Reference 38



2 V5 – 3/16

Peeled Wearlayer



FLOORING OPTIONS

Thickness

1/2" 3.5mm Wearlayer

Core

Multi-ply Hardwood

Plank Widths

3", 4" and 5"

Lengths

1' to 8'

Grades

Red Oak – Select Hickory – 1 & Better

Finishes

Two-Tone Stain

Matte UV Aluminum Oxide

Surface Treatments

Wire Brushed

Machining

Micro Bevel Tongue and Groove End Matched

Installations

Nail, Staple, Glue or Float

owens-flooring.com







FLOORING OPTIONS

Thickness

1/2" 2.5mm Wearlayer

Core

Multi-ply Hardwood

Plank Widths

6", 7" and 8"

Lengths

1' to 8'

Grades

Includes natural splits and sound-filled knots approximately 1-1/4" max

Finishes

Matte UV Aluminum Oxide

Machining

Micro Bevel Tongue and Groove End Matched


Installations

Nail, Staple or Glue
















Plank floor. COLLECTION

FLOORING OPTIONS

UNFINISHED & PREFINISHED PLANKFLOOR

Thickness

5/8" 4.5mm Wearlayer

Core

Multi-ply Hardwood

Plank Widths

2-1/4", 3", 4", 5" and 6"

Lengths

1' to 8'

Grades

See page 37

Finishes

Satin UV Aluminum Oxide *Prefinished only.*

Machining

End Matched
Square Edge
Unfinished only.
Micro Bevel (3/64" reveal)
Prefinished only.

Tongue and Groove

Installations

Nail, Staple or Glue
Float (only recommended in 3-5" widths)

CUSTOM PLANKFLOOR

Thickness

3/4" 4.5mm Wearlayer 1/2" 2.5mm Wearlayer 1/2" 3.5mm Wearlayer

Core

Multi-ply Hardwood

Plank Widths

7" and 8"

Lengths

Combinations up to 10' (available in 5/8" thickness or widths up to 5" in 3/4" thickness)

Finishes


High Gloss UV Aluminum Oxide Matte UV Aluminum Oxide

Machining

Chamfer Bevel (7/64" reveal) Grand Bevel (13/64" reveal) Radius (1/8" reveal) All Unfinished only.

Installations

Nail, Staple or Glue Float (only recommended in 3–5" widths)





Northern Red Oak

UNFINISHED PLANKFLOOR







PREFINISHED PLANKFLOOR ESSENTIALS











PREFINISHED PLANKFLOOR DESIGNER SERIES
























PREFINISHED PLANKFLOOR DESIGNER SERIES



Unfinished Plankfloor Collection American Black Walnut – Natural Distressed and Stained during Installation 3", 4" & 6" widths



Plankfloor COLLECTION




PREFINISHED PLANKFLOOR **ESSENTIALS**











Plankfloor C O L L E C T I O N

PREFINISHED PLANKFLOOR

White Oak



NATURAL Essentials



NATURAL R/Q SAWN Essentials



Essentials

KHAKI RUSSET



BURNISHED LEATHER



SORREL Essentials



UNFINISHED PLANKFLOOR







1COM/CHARACTER

1COM/CHARACTER

SELECT R/Q SAWN

Make Plankfloor Yours

The beauty of wood is captured by its uniqueness. Each species may contain variations in grain, color, marking and character. Photos in this catalog are for your creative purposes only. Actual floor colors and character will vary. Please use this catalog to dream and plan. Then, make Plankfloor yours.

Northern Red Oak





NATURAL R/Q SAWN Essentials





RUSSET

Essentials

Essentials

BURNISHED LEATHER



SORREL



PREMIUM

WISCONSIN WHEAT PREMIUM



SELECT

1COM/CHARACTER



R/Q SAWN



R/Q SAWN

1COM/CHARACTER R/Q SAWN





AUTUMN SUNSET SUN KISSED BEACH Designer



RIVER ROCK Designer



EVENING TWILIGHT Designer



Designer



Northern Hard Maple



NATURAL Essentials



KHAKI Essentials



RUSSET Essentials



LEATHER



SORREL Essentials



SELECT WHITE



2 & BETTER



AUTUMN SUNSET SUN KISSED BEACH EVENING TWILIGHT Designer



Designer



Designer



SCENIC TRAIL Designer



Designer



SALTED CARAMEL Designer

Hickory



NATURAL Essentials



KHAKI Essentials





LEATHER



SORREL Essentials



1 & BETTER

CHARACTER

American Black Walnut



WARM CHOCOLATE





35

Moderate Significant

PREFINISHED AND UNFINISHED PLANKFLOOR CONTINUED

NATURAL

PREFINISHED UNFINISHED

NATURAL Essentials

PREFINISHED UNFINISHED





NATURAL SELECT Essentials



American

Cherry

NATURAL SELECT

Essentials

Sapele



NATURAL

SELECT

Eucalyptus



NATURAL Essentials

SELECT

TRUECHARACTER COLLECTION

Northern **Hard Maple**



NATURAL

Northern **Red Oak**



NATURAL

Hickory



NATURAL



NATURAL

American White Oak Black Walnut







NATURAL

American

Cherry

GENUINE LIVING COLLECTION*

Northern **Red Oak**



BUNGALOW Select



LOFT Select



OCEAN VIEW COTTAGE Select

GRADES

	Color Variation	Knots	Character	Hardness**	Widths
White Oak					
Premium	0	0	0		
Select			0		
1Com/Character	•				
Rift/Quartered				1360	2-1/4", 3", 4", 5", 6", 7" & 8"
R/Q Select	•	•	0		
R/Q 1Com/Character					
Northern Red Oak					
Wisconsin Wheat Premium	0	0	0		
Select	•		0		
1Com/Character	•	•	•		
Rift/Quartered				1290	2-1/4", 3", 4", 5", 6", 7" & 8"
R/Q Select		•	0		
R/Q 1Com/Character	•				
Northern Hard Maple					
Wisconsin Select White	\bigcirc		0		
Salted Caramel	0	•	•	1450	2-1/4", 3", 4", 5", 6", 7" & 8"
2 & Better					
Hickory					
1 & Better			0	1820	2-1/4", 3", 4", 5", 6", 7" & 8"
Character				1020	2-1/4, 3, 4, 3, 0, 7 & 0
American Black Walnut					
Warm Chocolate	0	•	•		
Select	•	•	0	1010	3", 4", 5", 6", 7" & 8"
Natural	•				
American Cherry					
Natural	•	0	0	950	3", 4", 5", 6", 7" & 8"
Brazilian Cherry					
Select	•	\otimes	0	2350	3", 4", 5", 6", 7" & 8"
Eucalyptus					
Select	•	\otimes	0	1420	3", 4", 5", 6", 7" & 8"
Santos Mahogany					
Select	•	•	•	2200	3", 4", 5", 6", 7" & 8"
Sapele					
Select	•	\otimes	0	1510	3", 4", 5", 6", 7" & 8"

^{**}Janka hardness scale measures the force needed to embed a .444-inch steel ball into wood to half its diameter. This measurement is a helpful guideline in determining the wear and durability of a floor.

FLEXIBLE AND EASY INSTALLATION

What makes plankfloor so unique? When it comes to versatility and stability, few floors compare to plankfloor. Its **stability** is directly tied to its multi-layer construction, and It can be trusted for commercial installations or for use on any level of your home. Whether it's above, on or below grade, plankfloor is perfect in areas not normally recommended for 3/4" solid hardwood floors. It is even warrantied over in-floor radiant heat systems. **Installation versatility is clearly a "Plankfloor Advantage."**

Versatile Installation Options

Choose the best method of application for your subfloor. Glue it to concrete, float it over an existing floor or staple it onto subfloor.



Nail or Staple



loat*

For helpful installation instructions go to: www.quanex.com/Products/Wood-Flooring/Installation.aspx

Only recommended for 3-5" width:

Specially designed to nest the nail head and to keep glue from squeezing out on the face.




Where can you install Owens Plankfloor?




EDGE TREATMENTS

Looking to highlight your wide Plankfloor with added textural interest? Select one of Owens' treatments to customize your floor for the look you've always wanted. If you are custom finishing your floor before installation, a bevel is a helpful tool to ensure a flawless match. Whatever width, Plankfloor has designs to fit your needs.




Standard Plankfloor






Chamfer Bevel (7/64" reveal)



Grand Bevel (13/64" reveal)



Radius (1/8" reveal)

Edge treatments available in all widths of Plankfloor Unfinished flooring.



41

OWENS QUALITY

While other manufacturers promise quality, nothing beats Owens. The Owens Standard requires scientific testing and an **uncompromising commitment to quality.**


Inspection

In cooperation with suppliers, **Owens** has established strict incoming raw material specifications. A National Hardwood Lumber Association (NHLA) graduate lumber inspector, on staff, checks thickness, grade, width, length, stress and moisture content of ALL incoming lumber. The plywood used is exterior grade Baltic Birch. Its multi-layered construction is very stable and is free of large voids found in competitors' products.



Plywood cores are available in solid strip and/or finger jointed. This structurally solid joint prevents internal fracture and ensures that no "white lines" appear on the face of prefinished product.





Oven Test



No Delamination

Inside Plankfloor; what you see is 100% adhesive coverage — not spotty extruded adhesive lines Owens' proprietary lamination process is monitored by over 40 critical measurements and utilizes a waterresistant PUR adhesive. Owens' floors simply don't delaminate.

Glue bond tests are performed daily utilizing the ANSI/HPVA 3-cycle water soak and oven test method. We have even successfully tested our product with beer to demonstrate that it is suitable for use in bars and restaurants.

Minimize Seasonal Changes



Crossbanded plywood creates a stable platform for the solid wood surface. When sealed together, the adhesive creates a moisture barrier which minimizes seasonal changes.

Tested Durability



A warrantied durable factory finish and high quality lamination pair to create a stunning floor suitable for any light commercial application.

Consistent Heavy Wearlayer



No Aggressive Sanding Required

Plankfloor is calibration sanded at the factory. This means virtually no overwood! Typically, Plankfloor can be screened and finished with a third less labor versus the typical three-step process. This leaves more wear layer for future sandings.



 $_{10}$

FLOOR CARE AND MAINTENANCE

Caring for Your Floors

Your new wood floor is an important investment and must be properly cared for and maintained for you to enjoy its full life and beauty. The following care and maintenance tips should be followed to obtain the **full benefit** of your wood floor and to ensure that our warranty will continue to apply.



1. Clean your wood floor with a vacuum, duster or broom at least weekly.

Don't use a vacuum that has beaters or hard attachment tips. Remember that grit will greatly increase wear and can damage your wood floor.

Don't use a wet mop to clean your floor. Moisture from wet mopping will damage your wood floor. Wipe up spills immediately.

2. Use an area rug in front of your sink and other appliances, and on high-traffic areas. Don't use a mat with a solid backing that will trap moisture between the mat and your floor.

Don't wear hard-soled or high-heel shoes on your wood floor. Hard soles and pointed heels can damage the floor. For the same reason, keep your pet's nails trimmed to avoid scratch marks.





3. To avoid damage to your wood floor, keep the relative humidity in your home between 35% and 55% to reduce the risk of excessive expansion or contraction. Use pads on the ends of furniture legs to avoid denting or scratching your wood floor.


If you have to move heavy objects, such as furniture or appliances, over your wood floor, use a hard barrier, such as a board, on the floor and move the item across the barrier instead of sliding it directly on the floor.

4. Don't slide the barrier as you move the item. If you have furniture or appliances on casters, replace small or hard casters with casters made of wide, soft rubber. Never allow water or cleaners to pool or sit on top or soak into your wood floor. Moisture can damage the floor, and some cleaners are too harsh to use on the floor.

Don't use ammonia-based cleaners, oil-based soaps, bleaches, detergents, abrasive soaps or cleaners, waxes, acidic cleaners, or acrylic products on your wood floor, and avoid using solutions that must be combined with water. Use only hardwood floor cleaning solutions from reputable manufacturers such as BonaKemi, Basic Coatings, Minwax, or equivalent manufacturers to clean your wood floor.









35 years residential and **5 years** light commercial on smooth prefinished product. **15 years** residential and **3 years** light commercial on distressed prefinished.

For the full warranty, scan the QR code above or visit **owens-flooring.com**.











